



## Series Mini-RAP

### Technical data

Working temperature: -20°C +70°C  
Maximum working pressure: 10 bar  
Fluid: Compressed air (others fluids on requests)  
Nichel-plated brass body, Brass grip, Silicone free NBR gaskets  
Thread: Cylindrical with O-Ring  
Maximum fixing torque for fittings  
Thread: M3: 0,4 Nm  
Thread: M6 and M6x0,75: 1,3 Nm


### Main characteristics

1. Can be inserted and extracted with one hand
2. Suitable for tube Rilsan, Polyurethane, Nylon, Polyethylene
3. Supercompact
4. Extremely lightweight yet sturdy
5. O-Ring provided with his own seat to ensure seal with polished surface
6. Suitable for vacuum applicatio



RDR Straight male adaptor (parallel)


Coding: RDR3.40-MH05



RDR3.40-MH05

RDR Straight male adaptor (parallel)

Coding: RDR6.40-




CODE	ØD	G	ØC	H	L	Ø
RDR6.40-MH12	4	M6	6,8	12	25	2
RDR6.40-FH12	4	M6x0,75	6,8	12	25	2

	VERSION		
	MH12	=	M6,
	H=12mm		
	FH12	=	M6x0,75, H=12mm

RDR6.40-

RGR Complete single banjo with stem


Coding: RGR3.40-MH05



RGR3.40-MH05

RGR Complete single banjo with stem

Coding: RGR6.40-



CODE	ØD	G	ØA	H	L1	L	Ø
RGR6.40-MH12	4	M6	2	12	24,3	14,5	2
RGR6.40-FH12	4	M6x0,75	2	12	24,3	14,5	2

	VERSION		
	MH12	=	M6,
	H=12mm		
	FH12	=	M6x0,75, H=12mm

RGR6.40-